

STAINLESS STEEL FLEXIBLE CORRUGATED CONNECTORS

SPECIFICATIONS

- ▶ Stainless steel 304 (ASTM A240) CSSTNomina
- ▶ Chrome-plated brass Hpb58-3 fittings
- ▶ High-quality EPDM gasket
- ▶ Up to 125 psig working pressure
- ▶ Up to 189 psig intermittent impulse pressure
- ▶ -40°F to 180°F (82°C) temperature
- ▶ 2.5" minimum bend radius
- ▶ 100% leak tested

APPLICATIONS

- ▶ Water supply, water softeners, water heaters, etc.



Item No.	Description	Master
CFC75X12SS	¾" FIP X ¾" FIP X 12"	25
CFC75X18SS	¾" FIP X ¾" FIP X 18"	25
CFC75X24SS	¾" FIP X ¾" FIP X 24"	25
CFC75X1X18SS	¾" FIP X 1" FIP X 18"	15
CFC75X1X24SS	¾" FIP X 1" FIP X 24"	15
CFC1X12SS	1" FIP X 1" FIP X 12"	15

Item No.	Description	Master
CFC1X18SS	1" FIP X 1" FIP X 18"	15
CFC1X24SS	1" FIP X 1" FIP X 24"	15
CFC125X18SS	1¼" FIP X 1¼" FIP X 18"	10
CFC125X24SS	1¼" FIP X 1¼" FIP X 24"	10
CFC150X18SS	1½" FIP X 1½" FIP X 18"	5
CFC2X18SS	2" FIP X 2" FIP X 18"	5

QUALITY, SERVICE & SOLUTIONS

VISIT OUR WEBSITE AT
WWW.BAKERWATERSYSTEMS.COM
for other quality filtration and water system products

CAMPBELL MFG 127 East Spring Street
Bechtelsville, PA 19505
Phone: 800-523-0224 Fax: 610-369-3580
Email: moreinfo@campbellmfg.com

